

# Tandhan Power



**24 Month Warranty \***  
(FOC)  
\* T&C Apply

Excellent starting ability with higher cranking power to weight ratio

High charge retention characteristics with ability to perform even under partial state-of-charge condition

Superior maintenance free characteristics through advanced Ca-Ca technology requiring topping up once only in 9 months under standard operating condition

Battery size rationalized to suit different Genset ratings

Special lid design makes the battery spill-resistant

Vent caps with advanced flame arrestors and micro porous filter disc to arrest acid fumes

Excellent storage life

Delivered factory charged and in ready-to-use condition

## Technical Specifications of Exide Genplus Batteries

Battery Nomenclature	Capacity (Ah) 20Hr (Ref)	Maximum Overall Dimensions (MM)			Nominal Filled Weight (KG)	Electrolyte Volume (LITRES)	Charging Current (A)	CCA At - 18°C As Per		Genset KVA Rating	Voltage System	Battery Layout
		L	W	H				IEC	SAE			
FGP0-GP110D31R	90	305	173	225	22.2	5	5.5	576	720	5 - 160	12V	Right Layout -□□□□+
FGP0-GP110D31L	90	305	173	225	22.2	5	5.5	576	720	82 - 380	24V	Left Layout -□□□□+
FGP0-GP115E41L	105	410	176	233	28.1	6.1	6.5	660	825	380 - 1010	24V	Left Layout -□□□□+